


148 152 13 706 | anthracite

multi.flood
projector
LED | 112 W 3000 K



- projector multi.flood
- with mounting bracket
- for wall-, ground or pole-mounting
- with LED 15725 lm
- colour temperature: 3000 K
- colour rendering index: CRI >80
- L90 / B10 (100.000 / ta 25°C)
- SDCM < 4
- net luminous flux: 11630 lm
- total load: 112 W
- luminous efficacy: 103,8 lm/W
- axisymmetric light distribution
- distance to illuminating surface 2,5 up to 7 meters
- attached LED power unit, electronic, 220-240 V, 0/50/60 Hz
- overvoltage protection 6KV
- power supply: connecting terminal 3x2,5 mm²
- with a cord connection for power supply cord H07RN-F 3G 1.5 mm²
- housing of die cast aluminium
- safety glass, clear
- stainless steel mounting bracket
- length: 340 mm, width: 340 mm, height: 164 mm
- weight: 10,5 kg
- protection rating: IP65
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- maximum ambient temperature: 35 °C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: anthracite (RAL7016)
- 148 152 13 706
